

Claims

What is claimed is:

1. An optical identification element, comprising:
5 an optical substrate;
at least a portion of said substrate having at least one diffraction grating
disposed therein, said grating having at least one refractive index pitch superimposed
at a common location;
the grating providing an output optical signal when illuminated by an incident
10 light signal; and
said optical output signal being indicative of a code.
2. The apparatus of claim 1 wherein said substrate is made of a glass
material.
- 15 3. The apparatus of claim 1 wherein said code comprises a plurality of
bits.
4. The apparatus of claim 1 wherein the number of pitches is indicative of
the number of said bits in said code.
5. The apparatus of claim 1 wherein said substrate has a length that is less
20 than about 500 microns.
6. The apparatus of claim 1 wherein said substrate has a cylindrical
shape.
7. The apparatus of claim 1 wherein said grating is a blazed grating.
8. The apparatus of claim 1 wherein said code comprises a plurality of
25 bits, each bit having a plurality of states.
9. The apparatus of claim 1 wherein said substrate has a reflective coating
disposed thereon.
10. The apparatus of claim 1 wherein said substrate is has a magnetic or
electric charge polarization.

11. The apparatus of claim 1 wherein said substrate has a grating region where said grating and a non-grating region where said grating is not located; and wherein said substrate has a plurality of grating regions.

5 12. The apparatus of claim 1 wherein said substrate has geometry having holes therein.

13. The apparatus of claim 1 wherein said substrate is has a geometry having protruding sections.

14. The apparatus of claim 1 wherein at least a portion of said substrate is has an end cross sectional geometry selected from the group: circular, square, rectangular, elliptical, clam-shell, D-shaped, and polygon

15. The apparatus of claim 1 wherein at least a portion of said substrate is has a side view geometry selected from the group: circular, square, rectangular, elliptical, clam-shell, D-shaped, and polygon.

16. The apparatus of claim 1 wherein at least a portion of said substrate is has a 3-D shape selected from the group: sphere, a cube, a pyramid.

17. The apparatus of claim 1 wherein said code comprises at least a predetermined number of bits, said number being: 3, 5, 7, 9, 10, 12, 14, 16, 18, 20, 24, 28, 30, 40, 50, or 100.

18. A microparticle comprising:
20 an optical substrate;
at least a portion of said substrate having at least one diffraction grating disposed therein, said grating having at least one refractive index pitch superimposed at a common location;
the grating providing an output optical signal when illuminated by an incident
25 light signal; and
said optical output signal being indicative of a code in said substrate.

19. A method of reading a code in an optical identification element, comprising:

obtaining an optical substrate at least a portion of which having a diffraction grating with one or more refractive index pitches superimposed at a common location;
and

5 illuminating said substrate with incident light, said substrate providing an output light signal;

reading said output light signal and detecting a code therefrom.

10